

BUZ24

GENERAL DESCRIPTION


N-channel enhancement mode field-effect power transistor in a metal envelope.

This device is intended for use in Switched Mode Power Supplies (SMPS), motor control, welding, DC/DC and DC/AC converters, and in general purpose switching applications.

QUICK REFERENCE DATA


SYMBOL	PARAMETER	MAX.	UNIT
V _{DS}	Drain-source voltage	100	V
I _D	Drain current (d.c.)	32	A
P _{tot}	Total power dissipation	125	W
R _{DS(ON)}	Drain-source on-state resistance	0,06	Ω

MECHANICAL DATA



Notes

1. Observe the general handling precautions for electrostatic-discharge sensitive devices (ESDs) to prevent damage to MOS gate oxide.
2. Accessories supplied on request: refer to Mounting instructions for TO3 envelopes.



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

Quality Semi-Conductors

RATINGS

Limiting values in accordance with the Absolute Maximum System (IEC 134)

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V _{DS}	Drain-source voltage	—	—	100	V
V _{DGR}	Drain-gate voltage	R _{GS} = 20 kΩ	—	100	V
±V _{GS}	Gate-source voltage	—	—	20	V
I _D	Drain-current (d.c.)	T _{mb} = 25 °C	—	32	A
I _D	Drain current (d.c.)	T _{mb} = 100 °C	—	20,2	A
I _{DM}	Drain current (pulse peak value)	T _{mb} = 25 °C	—	125	A
P _{tot}	Total power dissipation	T _{mb} = 25 °C	—	125	W
T _{stg}	Storage temperature	—	−55	150	°C
T _j	Junction temperature	—	—	150	°C

THERMAL RESISTANCES

From junction to mounting base	R _{th j-mb} = 1,0 K/W
From junction to ambient	R _{th j-a} = 35 K/W

STATIC CHARACTERISTICS

T_{mb} = 25 °C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V _{(BR)DSS}	Drain-source breakdown voltage	V _{GS} = 0 V; I _D = 0,25 mA	100	—	—	V
V _{GS(TO)}	Gate threshold voltage	V _{DS} = V _{GS} ; I _D = 1 mA	2,1	3,0	4,0	V
I _{DSS}	Zero gate voltage drain current	V _{DS} = 100 V; V _{GS} = 0 V; T _j = 25 °C	—	20	250	μA
I _{DSS}	Zero gate voltage drain current	V _{DS} = 100 V; V _{GS} = 0 V; T _j = 125 °C	—	0,1	1,0	mA
I _{GSS}	Gate source leakage current	V _{GS} = ±20 V; V _{DS} = 0 V	—	10	100	nA
R _{DS(ON)}	Drain-source on-state resistance	V _{GS} = 10 V; I _D = 16 A	—	0,045	0,06	Ω

DYNAMIC CHARACTERISTICS

T_{mb} = 25 °C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
g _{fs}	Forward transconductance	V _{DS} = 25 V; I _D = 16 A	6,0	10,0	—	S
C _{iss}	Input capacitance	V _{GS} = 0 V; V _{DS} = 25 V; f = 1 MHz	—	1500	2000	pF
C _{oss}	Output capacitance		—	800	1200	pF
C _{rss}	Feedback capacitance		—	300	500	pF
t _{d on}	Turn-on delay time	V _{DD} = 30 V; I _D = 3 A;	—	30	45	ns
t _r	Turn-on rise time	V _{GS} = 10 V; R _{GS} = 50 Ω;	—	80	120	ns
t _{d off}	Turn-off delay time	R _{gen} = 50 Ω	—	330	430	ns
t _f	Turn-off fall time		—	170	220	ns
L _d	Internal drain inductance	Measured from contact screw on header closer to source pin and centre of die	—	5,0	—	nH
L _s	Internal source inductance	Measured from source lead 6 mm from package to source bond pad	—	12,5	—	nH

REVERSE DIODE RATINGS AND CHARACTERISTICS $T_{mb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
I_{DR}	Continuous reverse drain current	$T_{mb} = 25\text{ }^{\circ}\text{C}$	—	—	32	A
I_{DRM}	Pulsed reverse drain current	$T_{mb} = 25\text{ }^{\circ}\text{C}$	—	—	125	A
V_{SD}	Diode forward on-voltage	$I_F = 64\text{ A}; V_{GS} = 0\text{ V};$ $T_j = 25\text{ }^{\circ}\text{C}$	—	1,5	2,0	V
t_{rr}	Reverse recovery time	$I_F = 32\text{ A}; T_j = 25\text{ }^{\circ}\text{C}$ $-dI_F/dt = 100\text{ A}/\mu\text{s};$ $T_j = 25\text{ }^{\circ}\text{C}; V_{GS} = 0\text{ V};$	—	200	—	ns
Q_{rr}	Reverse recovery charge	$V_R = 30\text{ V}$	—	1,6	—	μC

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.